



Swage Nipples

Concentric Style

Advantages

- Zinc coated for improved weather resistance
- ASTM A106 Grade B Seamless Pipe
- Our Swage Nipples have heat numbers for traceability
- NPT threads per ASME B1.20.1
- EUE 8-Rd. Threads Available



Swage Nipples Offering Matrix - Thd/Thd

	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"
1/4" Hex	O														
3/8" Hex	O	O													
1/2" Hex		+	O +	O +											
3/4" Hex			O	O +											
1" Hex	O	O	O +	O +	O +										
1 1/4"						O +				+					
1 1/2"				O	O	O	O								
2"				O	O	X O*	X O	X O						+	
2 1/2"						X O	X O	X O	X O						
3"						X O		X O	X O*	X O					
4"						X O	O	X O	X O*	X O	X O				
5"												X O			
6"									X O	X O	X O	X O	X O		
8"									X* O*	X O	X O	X O		X O	
10"															X

X = Offered in STD Schedule 40 O = Offered in XH Schedule 80 + = Offered in XXH

* Available in Beval x Threaded

2UP 8R X 2LP X 6"STD J55 TUBING NIPPLE

2-1/2UP 8R X 2UP 8R STD J55 TUBING SWAGE



Swage Nipples

Concentric Style



CNC Flow Control - Headquarters
10350 Clay Road, Suite 250
Houston, TX 77041
Toll-Free: 844.398.6449

CNC Flow Control - Permian Basin
1100 W IH 20
Odessa, TX 79763
Main Line: 432.276.7640

Website: www.cncflowcontrol.com
More Info: info@cncflowcontrol.com

Follow us:

